

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 05/13/2016

Revision date: 05/13/2016

Supersedes: 05/13/2016

Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : QUICK DRY ALUMINUM
 Product code : 758097

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Solventborne Coating

1.3. Details of the supplier of the safety data sheet

Rodda Paint Co.
 6107 North Marine Drive
 Portland, Oregon 97203 - US
 T (503) 521-4300
www.rodmapaint.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flammable liquids Category 2	Highly flammable liquid and vapor
Germ cell mutagenicity Category 1B	May cause genetic defects
Carcinogenicity Category 1B	May cause cancer
Specific target organ toxicity (repeated exposure) Category 2	May cause damage to organs through prolonged or repeated exposure
Hazardous to the aquatic environment - Acute Hazard Category 2	Toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 3	Harmful to aquatic life with long lasting effects

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Highly flammable liquid and vapor
 May cause genetic defects
 May cause cancer
 May cause damage to organs through prolonged or repeated exposure
 Toxic to aquatic life
 Harmful to aquatic life with long lasting effects

Precautionary statements (GHS-US) :

Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Keep away from heat, hot surfaces, open flames, sparks. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical, lighting, ventilating equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Do not breathe mist, spray, vapors
 Avoid release to the environment
 Wear eye protection, protective clothing, protective gloves
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 If exposed or concerned: Get medical advice/attention
 Get medical advice/attention if you feel unwell
 In case of fire: Use ABC-powder, foam, sand to extinguish

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Store in a well-ventilated place. Keep cool
Store locked up
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
VM&P NAPHTHA	(CAS No) 8032-32-4	40.7	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
SOLVENT NAPHTHA, LIGHT AROMATIC	(CAS No) 64742-95-6	8.3	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
MINERAL SPIRITS	(CAS No) 64741-65-7	6.6	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
XYLENE	(CAS No) 1330-20-7	6.3	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315
TRIMETHYLBENZENE	(CAS No) 95-63-6	3	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 STOT SE 3, H335 Aquatic Chronic 2, H411
ETHYLBENZENE	(CAS No) 100-41-4	1.3	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Asp. Tox. 1, H304

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Highly flammable liquid and vapor.
Reactivity : Highly flammable liquid and vapor.

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe vapors, mist, spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe vapors, mist, spray.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

VM&P NAPHTHA (8032-32-4)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	350 mg/m ³
NIOSH	NIOSH REL (ceiling) (mg/m ³)	1800 mg/m ³
MINERAL SPIRITS (64741-65-7)		
Not applicable		
XYLENE (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
ETHYLBENZENE (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ETHYLBENZENE (100-41-4)		
OSHA	OSHA PEL (TWA) (mg/m ³)	435 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
IDLH	US IDLH (ppm)	800 ppm (10% LEL)
NIOSH	NIOSH REL (TWA) (mg/m ³)	435 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	100 ppm
NIOSH	NIOSH REL (STEL) (mg/m ³)	545 mg/m ³
NIOSH	NIOSH REL (STEL) (ppm)	125 ppm
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)		
Not applicable		
TRIMETHYLBENZENE (95-63-6)		
NIOSH	NIOSH REL (TWA) (mg/m ³)	125 mg/m ³
NIOSH	NIOSH REL (TWA) (ppm)	25 ppm

8.2. Exposure controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Personal protective equipment : Gloves. Safety glasses. Protective clothing. Respiratory protection of the dependent type.



Hand protection : Protective gloves.
Eye protection : Safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : Wear respiratory protection.
Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : silver
Odor : aromatic
Odor threshold : No data available
pH : No data available
Melting point : Not applicable
Freezing point : No data available
Boiling point : No data available
Flash point : 17 °C
Relative evaporation rate (butyl acetate=1) : No data available
Flammability (solid, gas) : No data available
Explosion limits : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Vapor pressure : No data available
Specific gravity : No data available
Relative vapor density at 20 °C : No data available
Specific gravity / density : 7.43 lb/gal
Solubility : No data available
Log Pow : No data available
Auto-ignition temperature : No data available

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: > 28 cSt
Viscosity, dynamic	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

In contact with water releases flammable gases.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Thermal decomposition generates : Carbon monoxide. Carbon dioxide. fume.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

VM&P NAPHTHA (8032-32-4)	
LC50 inhalation rat (ppm)	3400 ppm/4h
ATE US (gases)	3400.000 ppmV/4h
MINERAL SPIRITS (64741-65-7)	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h
XYLENE (1330-20-7)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	> 4350 mg/kg
LC50 inhalation rat (mg/l)	29.08 mg/l
ATE US (oral)	3500.000 mg/kg body weight
ATE US (dermal)	1100.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
ETHYLBENZENE (100-41-4)	
LD50 oral rat	3500 mg/kg
LD50 dermal rabbit	15400 mg/kg
LC50 inhalation rat (mg/l)	17.2 mg/l/4h
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	11.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
LD50 oral rat	8400 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (ppm)	3400 ppm/4h

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TRIMETHYLBENZENE (95-63-6)	
LD50 oral rat	3280 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (mg/l)	18 g/m ³ (Exposure time: 4 h)
ATE US (oral)	3280.000 mg/kg body weight
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	18.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

XYLENE (1330-20-7)	
IARC group	3 - Not Classifiable

ETHYLBENZENE (100-41-4)	
IARC group	2B - Possibly Carcinogenic to Humans
National Toxicity Program (NTP) Status	1 - Evidence of Carcinogenicity
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified

Specific target organ toxicity (repeated exposure) : May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Toxic to aquatic life.

MINERAL SPIRITS (64741-65-7)	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysisopsis bahia)

XYLENE (1330-20-7)	
LC50 fish 1	13.4 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	3.82 mg/l (Exposure time: 48 h - Species: water flea)
LC50 fish 2	2.661 - 4.093 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 2	0.6 mg/l (Exposure time: 48 h - Species: Gammarus lacustris)

ETHYLBENZENE (100-41-4)	
LC50 fish 1	11.0 - 18.0 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [static])
EC50 Daphnia 1	1.8 - 2.4 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	4.2 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss [semi-static])

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
LC50 fish 1	9.22 mg/l (Exposure time: 96 h - Species: Oncorhynchus mykiss)
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

TRIMETHYLBENZENE (95-63-6)	
LC50 fish 1	7.19 - 8.28 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	6.14 mg/l (Exposure time: 48 h - Species: Daphnia magna)

12.2. Persistence and degradability

No additional information available

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

XYLENE (1330-20-7)	
BCF fish 1	0.6 - 15
Log Pow	2.77 - 3.15
ETHYLBENZENE (100-41-4)	
BCF fish 1	15
Log Pow	3.2
TRIMETHYLBENZENE (95-63-6)	
Log Pow	3.63

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Waste disposal recommendations : Avoid release to the environment. Discharging into rivers and drains is forbidden. Dispose of contents/container to hazardous or special waste collection point in accordance with state and local regulations.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II
UN-No.(DOT) : UN1263
Proper Shipping Name (DOT) : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base
Class (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger
Dangerous for the environment : Yes
Marine pollutant : Yes



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

DOT Special Provisions (49 CFR 172.102)	: 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons) B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F) TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 60 L
DOT Vessel Stowage Location	: B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded
Emergency Response Guide (ERG) Number	: 128
Other information	: No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG)	: 1263
Proper Shipping Name (IMDG)	: PAINT
Class (IMDG)	: 3 - Flammable liquids
Packing group (IMDG)	: II - substances presenting medium danger

Air transport

UN-No. (IATA)	: 1263
Proper Shipping Name (IATA)	: Paint
Class (IATA)	: 3 - Flammable Liquids
Packing group (IATA)	: II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ALUMINUM	CAS No 7429-90-5	11.9%
XYLENE	CAS No 1330-20-7	6.3%
ETHYLBENZENE	CAS No 100-41-4	1.3%
TRIMETHYLBENZENE	CAS No 95-63-6	3%

VM&P NAPTHA (8032-32-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

VEHICLE NON-REPORTABLE

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ALUMINUM (7429-90-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 313 - Emission Reporting	1.0 % (dust or fume only)
MINERAL SPIRITS (64741-65-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
XYLENE (1330-20-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	100 lb
SARA Section 313 - Emission Reporting	1.0 %
ETHYLBENZENE (100-41-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA
CERCLA RQ	1000 lb
SARA Section 313 - Emission Reporting	0.1 %
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
TRIMETHYLBENZENE (95-63-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 313 - Emission Reporting	1.0 %

15.2. International regulations

CANADA

VM&P NAPHTHA (8032-32-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
ALUMINUM (7429-90-5)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 6 - Reactive Flammable Material
MINERAL SPIRITS (64741-65-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
XYLENE (1330-20-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
ETHYLBENZENE (100-41-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 2 - Flammable Liquid Class D Division 2 Subdivision A - Very toxic material causing other toxic effects Class D Division 2 Subdivision B - Toxic material causing other toxic effects
SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
TRIMETHYLBENZENE (95-63-6)	
Listed on the Canadian DSL (Domestic Substances List) inventory	
WHMIS Classification	Class B Division 3 - Combustible Liquid

EU-Regulations

VM&P NAPHTHA (8032-32-4)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
ALUMINUM (7429-90-5)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	
MINERAL SPIRITS (64741-65-7)	
Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances	

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

XYLENE (1330-20-7)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

ETHYLBENZENE (100-41-4)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

TRIMETHYLBENZENE (95-63-6)

Listed on the EEC inventory EINECS (European Inventory of Existing Commercial Chemical Substances) substances

National regulations

VM&P NAPHTHA (8032-32-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

ALUMINUM (7429-90-5)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

MINERAL SPIRITS (64741-65-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

XYLENE (1330-20-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Poisonous and Deleterious Substances Control Law
Pollutant Release and Transfer Register Law (PRTR Law)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

ETHYLBENZENE (100-41-4)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SOLVENT NAPHTHA, LIGHT AROMATIC (64742-95-6)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

TRIMETHYLBENZENE (95-63-6)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory
Listed on the Korean ECL (Existing Chemical List) inventory
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Pollutant Release and Transfer Register Law (PRTR Law)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican National Inventory of Chemical Substances)
Listed on CICR (Turkish Inventory and Control of Chemicals)

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

ETHYLBENZENE (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	54 µg/day

VM&P NAPHTHA (8032-32-4)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

ALUMINUM (7429-90-5)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

XYLENE (1330-20-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

ETHYLBENZENE (100-41-4)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

TRIMETHYLBENZENE (95-63-6)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 05/13/2016

QUICK DRY ALUMINUM

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer
H373	May cause damage to organs through prolonged or repeated exposure
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

RODDA PAINT CO. urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to understand the data contained in this SDS and any hazards associated with the product. This information is provided as a resource only and should not be taken as a warranty or representation for which RODDA PAINT CO. assumes legal responsibility. Unless otherwise specified, the data provided herein is valid only for the described material and may not be applicable for the product used in combination with any other materials or processes. The information contained within is believed to be accurate as of the effective date and compiled from sources believed to be reliable. The user assumes all responsibility of using and handling the product in accordance with applicable federal, state and local regulations.