



FINISH RIGHT

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification

1.1. Identification

Product form : Mixture
 Product name : SILICONE ALKYD ENAMEL GLOSS WHITE
 Product code : 758801

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Solventborne Coating

1.3. Details of the supplier of the safety data sheet

Rodda Paint Co.
 6107 North Marine Drive
 Portland, Oregon 97203
 T (503) 521-4300
www.roddapaint.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300 Chemtrec 24 Hour Emergency Telephone Number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 3	Flammable liquid and vapour
Skin Sens. 1	May cause an allergic skin reaction
Muta. 1B	May cause genetic defects (Inhalation, Dermal)
Carc. 1B	May cause cancer (Inhalation, Dermal)
STOT RE 1	Causes damage to organs through prolonged or repeated exposure (Dermal, Inhalation)

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

GHS08

Signal word (GHS-US) :

: Danger

Hazard statements (GHS-US) :

: Flammable liquid and vapor
 May cause an allergic skin reaction
 May cause genetic defects (Inhalation, Dermal)
 May cause cancer (Inhalation, Dermal)
 Causes damage to organs through prolonged or repeated exposure (Dermal, Inhalation)

Precautionary statements (GHS-US) :

: Obtain special instructions before use
 Do not handle until all safety precautions have been read and understood
 Keep away from heat, open flames, sparks. - No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/... equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Do not breathe dust/fume/gas/mist/vapors/spray
 Avoid breathing vapors, mist, fume
 Wash clothing, hands, forearms and face thoroughly after handling
 Do not eat, drink or smoke when using this product
 Contaminated work clothing must not be allowed out of the workplace
 Wear protective gloves, eye protection
 If on skin: Wash with plenty of soap & water
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
 If exposed or concerned: Get medical advice/attention
 Get medical advice/attention if you feel unwell
 Specific treatment (see ... on this label)

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

If skin irritation or rash occurs: Get medical advice/attention
Wash contaminated clothing before reuse
In case of fire: Use ABC-powder, carbon dioxide (CO₂), foam to extinguish
Store in a well-ventilated place. Keep cool
Store locked up
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation, a licensed hazardous-waste disposal contractor or collection site except for empty clean containers which can be disposed of as non-hazardous waste

2.3. Other hazards

Other hazards not contributing to the classification : None under normal conditions.

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	GHS-US classification
TITANIUM DIOXIDE	(CAS No) 13463-67-7	25.197389622 94554	Carc. 2, H351
MINERAL SPIRITS	(CAS No) 64741-65-7	20.191649210 441502	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
350B MINERAL SPIRITS	(CAS No) 8052-41-3	9.0436674186 2713	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
VM&P NAPHTHA	(CAS No) 8032-32-4	4.0283596519 4973	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
SOLVENT NAPHTHA, LIGHT AROMATIC	(CAS No) 64742-95-6	0.6662472669 87134	Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
METHYL ETHYL KETOXIME	(CAS No) 96-29-7	0.2819851756 36481	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Eye Dam. 1, H318 Skin Sens. 1, H317 Carc. 2, H351

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact : Rinse eyes with water as a precaution.
First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after skin contact : May cause an allergic skin reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

5.2. Special hazards arising from the substance or mixture

Fire hazard : Flammable liquid and vapor.
Reactivity : Flammable liquid and vapor.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : NO open flames, NO sparks, and NO smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe vapors, mist, fume.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe vapors, mist, fume. Avoid contact with skin and eyes.
Hygiene measures : Separate working clothes from town clothes. Launder separately. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.
Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

350B MINERAL SPIRITS (8052-41-3)		
ACGIH	ACGIH TWA (ppm)	100 ppm
OSHA	OSHA PEL (TWA) (mg/m ³)	2900 mg/m ³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm

TITANIUM DIOXIDE (13463-67-7)		
ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

TITANIUM DIOXIDE (13463-67-7)

OSHA

OSHA PEL (TWA) (mg/m³)

15 mg/m³ (total dust)

8.2. Exposure controls

Appropriate engineering controls

: Ensure good ventilation of the work station.

Personal protective equipment

: Dust/aerosol mask with filter type P1. Gloves. In case of splash hazard: safety glasses.



Hand protection

: Protective gloves.

Eye protection

: Safety glasses.

Skin and body protection

: Wear suitable protective clothing.

Respiratory protection

: Wear respiratory protection.

Environmental exposure controls

: Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

: Liquid

Color

: white

Odor

: aromatic

Odor threshold

: No data available

pH

: No data available

Melting point

: Not applicable

Freezing point

: No data available

Boiling point

: No data available

Flash point

: 24 °C

Relative evaporation rate (butyl acetate=1)

: No data available

Flammability (solid, gas)

: No data available

Explosion limits

: No data available

Explosive properties

: No data available

Oxidizing properties

: No data available

Vapor pressure

: No data available

Relative density

: No data available

Relative vapor density at 20 °C

: No data available

Specific gravity / density

: 1.17 g/cm³

Solubility

: No data available

Log Pow

: No data available

Auto-ignition temperature

: No data available

Decomposition temperature

: No data available

Viscosity

: ≈

Viscosity, kinematic

: 300 cSt

Viscosity, dynamic

: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions.

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

METHYL ETHYL KETOXIME (96-29-7)	
LD50 oral rat	930 mg/kg
LD50 dermal rabbit	1000 - 1800 mg/kg
ATE US (oral)	930.000 mg/kg body weight
ATE US (dermal)	1000.000 mg/kg body weight

VM&P NAPHTHA (8032-32-4)	
LC50 inhalation rat (ppm)	3400 ppm/4h
ATE US (gases)	3400.000 ppmV/4h

MINERAL SPIRITS (64741-65-7)	
LD50 oral rat	> 7000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 5.04 mg/l/4h

ALUMINUM HYDROXIDE (21645-51-2)	
LD50 oral rat	> 5000 mg/kg

SILICA (7631-86-9)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
LC50 inhalation rat (mg/l)	> 2.2 mg/l (Exposure time: 1 h)

TITANIUM DIOXIDE (13463-67-7)	
LD50 oral rat	> 10000 mg/kg

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : May cause genetic defects (Inhalation, Dermal).
Carcinogenicity : May cause cancer (Inhalation, Dermal).

SILICA (7631-86-9)	
IARC group	3 - Not Classifiable

TITANIUM DIOXIDE (13463-67-7)	
IARC group	2B - Possibly Carcinogenic to Humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity : Not classified
Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Causes damage to organs through prolonged or repeated exposure (Dermal, Inhalation).

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Aspiration hazard : Not classified
Symptoms/injuries after skin contact : May cause an allergic skin reaction.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.

METHYL ETHYL KETOXIME (96-29-7)	
LC50 fish 1	777 - 914 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])
EC50 Daphnia 1	750 mg/l (Exposure time: 48 h - Species: Daphnia magna)
LC50 fish 2	760 mg/l (Exposure time: 96 h - Species: Poecilia reticulata [static])

MINERAL SPIRITS (64741-65-7)	
EC50 Daphnia 1	2 mg/l (Exposure time: 48 h - Species: Mysidopsis bahia)

SILICA (7631-86-9)	
LC50 fish 1	5000 mg/l (Exposure time: 96 h - Species: Brachydanio rerio [static])
EC50 Daphnia 1	7600 mg/l (Exposure time: 48 h - Species: Ceriodaphnia dubia)

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

METHYL ETHYL KETOXIME (96-29-7)	
BCF fish 1	0.5 - 5.8
Log Pow	0.65 (at 25 °C)

SILICA (7631-86-9)	
BCF fish 1	(no bioaccumulation expected)

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description : UN1263 Paint (including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base), 3, II

UN-No.(DOT) : UN1263

Proper Shipping Name (DOT) : Paint
including paint, lacquer, enamel, stain, shellac solutions, varnish, polish, liquid filler, and liquid lacquer base

Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



Packing group (DOT) : II - Medium Danger
DOT Packaging Non Bulk (49 CFR 173.xxx) : 173
DOT Packaging Bulk (49 CFR 173.xxx) : 242
DOT Special Provisions (49 CFR 172.102) : 149 - When transported as a limited quantity or a consumer commodity, the maximum net capacity specified in 173.150(b)(2) of this subchapter for inner packaging may be increased to 5 L (1.3 gallons).
B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.
IB2 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized.
T4 - 2.65 178.274(d)(2) Normal..... 178.275(d)(3)
TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
TP8 - A portable tank having a minimum test pressure of 1.5 bar (150 kPa) may be used when the flash point of the hazardous material transported is greater than 0 C (32 F).
TP28 - A portable tank having a minimum test pressure of 2.65 bar (265 kPa) may be used provided the calculated test pressure is 2.65 bar or less based on the MAWP of the hazardous material, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.
DOT Packaging Exceptions (49 CFR 173.xxx) : 150
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 5 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 60 L
DOT Vessel Stowage Location : B - (i) The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel carrying a number of passengers limited to not more than the larger of 25 passengers, or one passenger per each 3 m of overall vessel length; and (ii) "On deck only" on passenger vessels in which the number of passengers specified in paragraph (k)(2)(i) of this section is exceeded.
Other information : No supplementary information available.

TDG

No additional information available

Transport by sea

UN-No. (IMDG) : 1263
Proper Shipping Name (IMDG) : PAINT
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : II - substances presenting medium danger

Air transport

UN-No. (IATA) : 1263
Proper Shipping Name (IATA) : Paint
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : II - Medium Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

MANGANESE COMPOUNDS	CAS No 7439-96-5	0.059418304866259%
XYLENE	CAS No 1330-20-7	0.009993709004807%
ETHYLBENZENE	CAS No 100-41-4	0.001998741800961%

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

METHYL ETHYL KETOXIME (96-29-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	T - T - indicates a substance that is the subject of a Section 4 test rule under TSCA.
VM&P NAPHTHA (8032-32-4)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
350B MINERAL SPIRITS (8052-41-3)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
MINERAL SPIRITS (64741-65-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
ALUMINUM HYDROXIDE (21645-51-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SILICA (7631-86-9)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
TITANIUM DIOXIDE (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2. International regulations

CANADA

METHYL ETHYL KETOXIME (96-29-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
VM&P NAPHTHA (8032-32-4)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
350B MINERAL SPIRITS (8052-41-3)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class B Division 3 - Combustible Liquid Class D Division 2 Subdivision B - Toxic material causing other toxic effects
MINERAL SPIRITS (64741-65-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
TITANIUM DIOXIDE (13463-67-7)	
Listed on the Canadian DSL (Domestic Substances List) inventory.	
WHMIS Classification	Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

EU-Regulations

No additional information available

National regulations

METHYL ETHYL KETOXIME (96-29-7)	
Listed on the AICS (the Australian Inventory of Chemical Substances) Listed on Inventory of Existing Chemical Substances (IECSC) Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory. Listed on the Korean ECL (Existing Chemical List) inventory. Listed on New Zealand - Inventory of Chemicals (NZIoC) Listed on Inventory of Chemicals and Chemical Substances (PICCS) Listed on INSQ (Mexican national Inventory of Chemical Substances) Listed on Turkish inventory of chemical	
VM&P NAPHTHA (8032-32-4)	
Listed on the AICS (the Australian Inventory of Chemical Substances) Listed on Inventory of Existing Chemical Substances (IECSC) Listed on the Korean ECL (Existing Chemical List) inventory. Listed on New Zealand - Inventory of Chemicals (NZIoC) Listed on Inventory of Chemicals and Chemical Substances (PICCS) Listed on the Canadian Ingredient Disclosure List Listed on INSQ (Mexican national Inventory of Chemical Substances) Listed on Turkish inventory of chemical	

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

350B MINERAL SPIRITS (8052-41-3)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

MINERAL SPIRITS (64741-65-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

ALUMINUM HYDROXIDE (21645-51-2)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

SILICA (7631-86-9)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on the Canadian Ingredient Disclosure List
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

TITANIUM DIOXIDE (13463-67-7)

Listed on the AICS (the Australian Inventory of Chemical Substances)
Listed on Inventory of Existing Chemical Substances (IECSC)
Listed on the Japanese ENCS (Existing & New Chemicals Substances) inventory.
Listed on the Korean ECL (Existing Chemical List) inventory.
Listed on New Zealand - Inventory of Chemicals (NZIoC)
Listed on Inventory of Chemicals and Chemical Substances (PICCS)
Listed on INSQ (Mexican national Inventory of Chemical Substances)
Listed on Turkish inventory of chemical

15.3. US State regulations

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer, developmental and/or reproductive harm

TITANIUM DIOXIDE (13463-67-7)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
Yes	No	No	No	

VM&P NAPHTHA (8032-32-4)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SILICONE ALKYD ENAMEL GLOSS WHITE

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

350B MINERAL SPIRITS (8052-41-3)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SILICA (7631-86-9)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

TITANIUM DIOXIDE (13463-67-7)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Sens. 1	Skin sensitization Category 1
STOT RE 1	Specific target organ toxicity (repeated exposure) Category 1
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H372	Causes damage to organs through prolonged or repeated exposure

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product