		Page: 1
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER


Recommended use of the chemical and restrictions on use

<p>Details of the supplier of the safety data sheet Niteo Products, LLC P.O. Box 191629 Dallas TX 75219 United States of America</p>	<p>Emergency telephone number CHEMTREC DIRECT 1-800-424-9300</p> <p>Product Information 1-844-696-4836</p>
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

- Flammable liquids : Category 2
- Acute toxicity (Oral) : Category 3
- Acute toxicity (Inhalation) : Category 3
- Acute toxicity (Dermal) : Category 3
- Skin irritation : Category 2
- Eye irritation : Category 2A
- Reproductive toxicity : Category 2
- Specific target organ systemic toxicity - single exposure : Category 1 (Central nervous system, Eyes)
- Specific target organ systemic toxicity - single exposure : Category 3 (Central nervous system)
- Specific target organ : Category 2 (Neurologic: other (neuropsychological effects,

		Page: 2
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER PY400354		Version: 1.2

systemic toxicity - repeated exposure (Inhalation)

auditory dysfunction and effects on colour vision))

Aspiration hazard : Category 1

GHS Label element

Hazard pictograms :



Signal Word : Danger

Hazard Statements :

- Highly flammable liquid and vapor.
- Toxic if swallowed, in contact with skin or if inhaled.
- May be fatal if swallowed and enters airways.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause drowsiness or dizziness.
- Suspected of damaging fertility or the unborn child.
- Causes damage to organs (Central nervous system, Eyes).
- May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction and effects on colour vision)) through prolonged or repeated exposure if inhaled.


Precautionary Statements :

Prevention:

- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
- Keep container tightly closed.
- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- Use only non-sparking tools.
- Take precautionary measures against static discharge.
- Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.
- Wash skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

- IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
- IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician. Rinse mouth.
- IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- IF INHALED: Remove person to fresh air and keep comfortable

		Page: 3
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

for breathing. Call a POISON CENTER or doctor/ physician.
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed: Call a POISON CENTER or doctor/ physician. Do NOT induce vomiting.
 If skin irritation occurs: Get medical advice/ attention.
 If eye irritation persists: Get medical advice/ attention.
 Take off contaminated clothing and wash before reuse.
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
 Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up.

Disposal:
 Dispose of contents/ container to an approved waste disposal plant.

Other hazards
 None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Defatter
 Chemical nature : Static Accumulator

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	Flam. Liq. 2; H225 STOT SE 3; H336 Asp. Tox. 1; H304 Aquatic Acute 2; H401 Aquatic Chronic 2; H411	44.30
METHANOL	67-56-1	Flam. Liq. 2; H225 Acute Tox. 3; H301 Acute Tox. 3; H331	36.88

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER


Version: 1.2

PY400354

		Acute Tox. 3; H311 STOT SE 1; H370	
TOLUENE	108-88-3	Flam. Liq. 2; H225 Skin Irrit. 2; H315 Eye Irrit. 2A; H319 Repr. 2; H361 STOT SE 3; H336 STOT RE 2; H373 Asp. Tox. 1; H304	9.95
ACETONE	67-64-1	Flam. Liq. 2; H225 Eye Irrit. 2A; H319 STOT SE 3; H336	8.88
n-HEPTANE	142-82-5	Flam. Liq. 2; H225 Skin Irrit. 2; H315 STOT SE 3; H336 Asp. Tox. 1; H304	1.77

SECTION 4. FIRST AID MEASURES

General advice : Move out of dangerous area.
Consult a physician.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may appear several hours later.
Do not leave the victim unattended.

		Page: 5
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		


- If inhaled : Move to fresh air.
Call a physician or poison control centre immediately.
Keep patient warm and at rest.
If unconscious place in recovery position and seek medical advice.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
Wash contaminated clothing before re-use.
If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water.
Remove contact lenses.
Protect unharmed eye.
- If swallowed : Get medical attention immediately.
Do NOT induce vomiting.
Rinse mouth with water.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material.

This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis.

This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:

- stomach or intestinal upset (nausea, vomiting, diarrhea)
- irritation (nose, throat, airways)
- temporary changes in mood and behavior
- loss of appetite
- muscle cramps
- pain in the abdomen and lower back

		Page: 6
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

Blurred vision
 Shortness of breath
 confusion
 irregular heartbeat
 cyanosis (causes blue coloring of the skin and nails from lack of oxygen)
 visual impairment (including blindness)
 Toxic if swallowed, in contact with skin or if inhaled
 May be fatal if swallowed and enters airways.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause drowsiness or dizziness.
 Suspected of damaging fertility or the unborn child.
 Causes damage to organs.
 May cause damage to organs through prolonged or repeated exposure if inhaled.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
 Water spray
 Foam
 Alcohol-resistant foam
 Carbon dioxide (CO₂)
 Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
 Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Aldehydes
 carbon dioxide and carbon monoxide
 organic compounds
 Hydrocarbons
- Specific extinguishing methods :
- Product is compatible with standard fire-fighting agents.

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Version: 1.2

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER

PY400354

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Remove all sources of ignition.
Use personal protective equipment.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information : Comply with all applicable federal, state, and local regulations.
Suppress (knock down) gases/vapours/mists with a water spray jet.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Open drum carefully as content may be under pressure.
Avoid formation of aerosol.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.
Take precautionary measures against static discharges.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER

Version: 1.2

PY400354

Container may be opened only under exhaust ventilation hood.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
No smoking.
Electrical installations / working materials must comply with the technological safety standards.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	TWA	500 ppm	OSHA_TRANS
		TWA	300 ppm	ACGIH
		TWA	2,000 mg/m3	OSHA_TRANS
METHANOL	67-56-1	TWA	1,370 mg/m3	ACGIH
		TWA	200 ppm	ACGIH
		STEL	250 ppm	ACGIH
		REL	200 ppm 260 mg/m3	NIOSH/GUIDE
		STEL	250 ppm 325 mg/m3	NIOSH/GUIDE
		PEL	200 ppm 260 mg/m3	OSHA_TRANS
TOLUENE	108-88-3	TWA	200 ppm 260 mg/m3	TN OEL
		STEL	250 ppm 325 mg/m3	TN OEL
		TWA	20 ppm	ACGIH
		REL	100 ppm 375 mg/m3	NIOSH/GUIDE
		STEL	150 ppm 560 mg/m3	NIOSH/GUIDE
		TWA	200 ppm	OSHA/Z2
ACETONE	67-64-1	Ceiling	300 ppm	OSHA/Z2
		MAX. CONC	500 ppm	OSHA/Z2
		TWA	500 ppm	ACGIH
		STEL	750 ppm	ACGIH

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

 Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER

Version: 1.2

PY400354

		REL	250 ppm 590 mg/m3	NIOSH/GUID E
		PEL	1,000 ppm 2,400 mg/m3	OSHA_TRA NS
		TWA	250 ppm	ACGIHLIS_P
		STEL	500 ppm	ACGIHLIS_P
		TWA	750 ppm 1,800 mg/m3	Z1A
		STEL	1,000 ppm 2,400 mg/m3	Z1A
n-HEPTANE	142-82-5	REL	85 ppm 350 mg/m3	NIOSH/GUID E
		Ceil_Time	440 ppm 1,800 mg/m3	NIOSH/GUID E
		PEL	500 ppm 2,000 mg/m3	OSHA_TRA NS
		TWA	400 ppm	ACGIH
		STEL	500 ppm	ACGIH


Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
METHANOL	67-56-1	methanol	Urine	Sampling time: End of shift.	15 mg/l	
Remarks:	Background, Nonspecific					
TOLUENE	108-88-3	o-Cresol, with hydrolysis	Creatinine in urine	Sampling time: End of shift.	0.3 mg/g	
Remarks:	Background					
		toluene	Urine	Sampling time: End of shift.	0.03 mg/l	
		toluene	Blood	Sampling time: Prior to last shift of work week.	0.02 mg/l	
ACETONE	67-64-1	acetone	Urine	Sampling time: End of shift.	50 mg/l	
Remarks:	Nonspecific					

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.

		Page: 10
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

- Hand protection
Material : neoprene
- Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.
- Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.
- Skin and body protection : Wear as appropriate:
impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Discard gloves that show tears, pinholes, or signs of wear.
Wear resistant gloves (consult your safety equipment supplier).
- Hygiene measures : Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
When using do not eat or drink.
When using do not smoke.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state : liquid
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- Boiling point/boiling range : 133 °F / 56 °C
(1,013.232 hPa)

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER


Version: 1.2

PY400354

Flash point	:	Calculated Phase Transition Liquid/Gas -4 °F / -20 °C
Evaporation rate	:	Calculated Flash Point No data available
Flammability (solid, gas)	:	No data available
Flammability (liquids)	:	Static Accumulating liquid
Flammability (liquids)	:	
Upper explosion limit	:	36 %(V) Calculated Explosive Limit
Lower explosion limit	:	1.05 %(V) Calculated Explosive Limit
Vapour pressure	:	307.9692 hPa (25 °C) Calculated Vapor Pressure
Relative vapour density	:	No data available
Relative density	:	No data available
Density	:	0.806 g/cm ³ (25 °C)
Solubility(ies)	:	
Water solubility	:	No data available
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Thermal decomposition	:	No data available
Viscosity	:	
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Oxidizing properties	:	No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No decomposition if stored and applied as directed.
Chemical stability	:	Stable under recommended storage conditions.
Possibility of hazardous	:	Vapours may form explosive mixture with air.

		Page: 12
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

reactions

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Acids
alkalis
aluminum
Amines
Ammonia
halogens
Lead
peroxides
Reducing agents
sodium
strong bases
Strong oxidizing agents
Zinc
Peroxides

Hazardous decomposition products : Aldehydes
carbon dioxide and carbon monoxide
formaldehyde-like
Hydrocarbons
organic compounds

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Toxic if swallowed, in contact with skin or if inhaled

Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:


Acute oral toxicity : LD 50 (Rat): > 8,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 3400 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD 50 (Rat): > 4,000 mg/kg

METHANOL:

Acute oral toxicity : LD L0 (Human): 300 mg/kg
Assessment: The component/mixture is classified as acute oral toxicity, category 3.

		Page: 13
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

Acute inhalation toxicity : LC 50 (Rat): 64000 ppm
Exposure time: 4 h

Assessment: The component/mixture is classified as acute inhalation toxicity, category 3.

Remarks: Slightly toxic by inhalation

Acute dermal toxicity : LD 50 (Rabbit): 12,800 mg/kg

Assessment: The component/mixture is classified as acute dermal toxicity, category 3.

TOLUENE:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC 50 (Rat): 8000 ppm
Exposure time: 4 h

Acute dermal toxicity : LD 50 (Rabbit): 12,124 mg/kg

ACETONE:

Acute oral toxicity : LD 50 (Rat, female): 5,800 mg/kg

Acute inhalation toxicity : LC 50 (Rat, female): 76 mg/l
Exposure time: 4 h

Acute dermal toxicity : LD 50 (Rabbit): > 7,426 mg/kg

n-HEPTANE:

Acute oral toxicity : LD 50 (Rat): Expected > 5,000 mg/kg
Remarks: Information given is based on data obtained from similar substances.

Acute inhalation toxicity : LC 50 (Rat, male and female): > 29.29 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Acute dermal toxicity : LD 50 (Rabbit): Expected > 2,000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.


Skin corrosion/irritation

Causes skin irritation.

Product:

Remarks: May cause skin irritation and/or dermatitis.

Result: Repeated exposure may cause skin dryness or cracking.

		Page: 14
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:
Result: Mildly irritating to skin

METHANOL:
Species: Rabbit
Result: Not irritating to skin

TOLUENE:
Result: Irritating to skin

ACETONE:
Result: Mildly irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.

n-HEPTANE:
Result: Irritating to skin

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:
Result: Mildly irritating to eyes

METHANOL:
Species: Rabbit
Result: Mildly irritating to eyes

TOLUENE:
Result: Irritating to eyes

ACETONE:
Result: Irritating to eyes

n-HEPTANE:
Result: Mildly irritating to eyes


Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

METHANOL:
Test Type: Maximisation Test (GPMT)
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406

		Page: 15
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

n-HEPTANE:
 Test Type: Maximisation Test (GPMT)
 Species: Guinea pig
 Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Not classified based on available information.

Components:

n-HEPTANE:
 Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
 Test species: rat hepatocytes
 Method: OECD Test Guideline 473
 Result: negative

: Test Type: Ames test
 Method: OECD Test Guideline 471
 Result: negative

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Suspected of damaging fertility or the unborn child.

Components:

TOLUENE:
 Reproductive toxicity - Assessment : Some evidence of adverse effects on development, based on animal experiments.

STOT - single exposure

May cause drowsiness or dizziness.
 Causes damage to organs (Central nervous system, Eyes).

Components:

METHANOL:
 Target Organs: Central nervous system, Eyes
 Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.


TOLUENE:
 Exposure routes: Inhalation
 Target Organs: Central nervous system
 Assessment: May cause drowsiness or dizziness.

ACETONE:
 Exposure routes: Inhalation
 Target Organs: Nervous system
 Assessment: May cause drowsiness or dizziness.

n-HEPTANE:
 Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

May cause damage to organs (Neurologic: other (neuropsychological effects, auditory dysfunction

		Page: 16
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

and effects on colour vision)) through prolonged or repeated exposure if inhaled.

Components:

TOLUENE:

Exposure routes: Inhalation

Target Organs: Neurologic: other (neuropsychological effects, auditory dysfunction and effects on colour vision)

Assessment: May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

May be fatal if swallowed and enters airways.

Components:

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC:

May be fatal if swallowed and enters airways.

TOLUENE:

May be fatal if swallowed and enters airways.

ACETONE:

May be harmful if swallowed and enters airways.

n-HEPTANE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

METHANOL:

Remarks: Central nervous system

Carcinogenicity:

IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER

Version: 1.2

PY400354

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

METHANOL:

Toxicity to fish : LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 18,000 - 20,000 mg/l
Exposure time: 96 h
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): > 10,000 mg/l
Exposure time: 48 h
Test Type: static test

TOLUENE:

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 5.5 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Water flea (Ceriodaphnia dubia)): 3.78 mg/l
Exposure time: 48 h
Remarks: Mortality

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (microalgae)): > 433 mg/l
End point: Growth inhibition
Exposure time: 96 h

NOEC (Scenedesmus quadricauda (Green algae)): > 400 mg/l
End point: Growth inhibition
Exposure time: 7 d

Toxicity to fish (Chronic toxicity) : NOEC (Oncorhynchus mykiss (rainbow trout)): 1.39 mg/l
Exposure time: 40 d
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Water flea (Ceriodaphnia dubia)): 0.74 mg/l
Exposure time: 7 d

ACETONE:

Toxicity to fish : LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss)): 4,740 - 6,330 mg/l
Exposure time: 96 h
Test Type: static test

LC 50 (Fathead minnow (Pimephales promelas)): 8,733 - 9,482 mg/l
Exposure time: 96 h
Test Type: flow-through test

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER

Version: 1.2

PY400354

- Toxicity to algae : NOEC (Microcystis aeruginosa): 530 mg/l
Exposure time: 8 d
Test Type: static test

- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 2,112 mg/l
Exposure time: 28 d
Test Type: flow-through test

- n-HEPTANE:
- Toxicity to daphnia and other aquatic invertebrates : EC 50 (Water flea (Daphnia magna)): 1.5 mg/l
Exposure time: 48 h
Test Type: static test

- LC 50 (Mysidopsis bahia (opossum shrimp)): 0.1 mg/l
Exposure time: 96 h
Test Type: semi-static test

- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Water flea (Daphnia magna)): 1 mg/l
Exposure time: 21 d
Test Type: static test
Test substance: WAF
Method: OECD Test Guideline 211
Remarks: Information given is based on data obtained from similar substances.

- Ecotoxicology Assessment
- Acute aquatic toxicity : Very toxic to aquatic life.


- Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

- Persistence and degradability**
- METHANOL:
- Biodegradability : Biodegradation: 99 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

- TOLUENE:
- Biodegradability : Result: Readily biodegradable

- ACETONE:
- Biodegradability : Result: Readily biodegradable
Biodegradation: 90.9 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

- n-HEPTANE:
- Biodegradability : Result: Readily biodegradable

		Page: 19
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

Bioaccumulative potential

METHANOL:

Partition coefficient: n-octanol/water : log Pow: -0.77

TOLUENE:

Bioaccumulation : Species: Ide, silver or golden orfe (Leuciscus idus)
 Bioconcentration factor (BCF): 94
 Exposure time: 3 d
 Concentration: 0.05 mg/l
 Method: Not reported

Partition coefficient: n-octanol/water : log Pow: 2.73

ACETONE:

Partition coefficient: n-octanol/water : log Pow: -0.24

n-HEPTANE:

Partition coefficient: n-octanol/water : log Pow: 4.66

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water courses or the soil.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.

 Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Version: 1.2

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER

PY400354

Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	------------------------------

U.S. DOT - ROAD

UN 1992	Flammable liquids, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

CFR_RAIL_C

UN 1992	Flammable liquids, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

U.S. DOT - INLAND WATERWAYS

UN 1992	Flammable liquids, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

TDG_ROAD_C

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

TDG_RAIL_C

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

TDG_INWT_C

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

INTERNATIONAL MARITIME DANGEROUS GOODS

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Version: 1.2

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER

PY400354

UN	1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, METHANOL)	3	(6.1)	II	MARINE POLLUTANT:(ALIPHATIC PETROLEUM NAPHTHA)
----	------	---	---	-------	----	---

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN	1992	Flammable liquid, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II
----	------	--	---	-------	----

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN	1992	Flammable liquid, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II
----	------	--	---	-------	----

MX_DG

UN	1992	LIQUIDO INFLAMABLE, TOXICO, N.E.P. (ACETONE, METHANOL)	3	(6.1)	II
----	------	--	---	-------	----

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Marine pollutant	yes
------------------	-----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
TOLUENE	108-88-3	1000	10026.670945

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

SARA 313 Component(s)
METHANOL 67-56-1 36.88 %

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Pyroil™ NON-CHLORINATED BRAKE PARTS
CLEANER

Version: 1.2

PY400354

TOLUENE 108-88-3 9.95 %

Pennsylvania Right To Know

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	30.00 - 50.00 %
METHANOL	67-56-1	30.00 - 50.00 %
TOLUENE	108-88-3	5.00 - 10.00 %
ACETONE	67-64-1	5.00 - 10.00 %
n-HEPTANE	142-82-5	1.00 - 5.00 %
BENZENE	71-43-2	0.00 - 0.10 %

New Jersey Right To Know

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	30.00 - 50.00 %
METHANOL	67-56-1	30.00 - 50.00 %
TOLUENE	108-88-3	5.00 - 10.00 %
ACETONE	67-64-1	5.00 - 10.00 %
n-HEPTANE	142-82-5	1.00 - 5.00 %

California Prop 65

WARNING! This product contains a chemical known to the State of California to cause cancer.

BENZENE	71-43-2
ETHYL BENZENE	100-41-4

WARNING: This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

METHANOL	67-56-1
TOLUENE	108-88-3
BENZENE	71-43-2

The components of this product are reported in the following inventories:

- TSCA : On TSCA Inventory
- DSL : All components of this product are on the Canadian DSL.
- AICS : On the inventory, or in compliance with the inventory
- NZIOC : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET

Revision Date: 07/31/2016

Print Date: 4/3/2017

SDS Number: R0253095

Version: 1.2

Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER

PY400354

- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 07/31/2016

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2*</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">3</td> </tr> <tr> <td style="background-color: yellow; color: black;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2*	FLAMMABILITY	3	PHYSICAL HAZARD	0
HEALTH	2*						
FLAMMABILITY	3						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IB

Full text of H-Statements referred to under sections 2 and 3.

		Page: 24
SAFETY DATA SHEET		Revision Date: 07/31/2016
		Print Date: 4/3/2017
		SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER		Version: 1.2
PY400354		

H225	Highly flammable liquid and vapor.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H305	May be harmful if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H333	May be harmful if inhaled.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H361d	Suspected of damaging the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.
H400	Very toxic to aquatic life.
H401	Toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.


Sources of key data used to compile the Safety Data Sheet
Internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.
Cefic, the European Chemical Industry Council.
ESIS European Chemical Substances Information System

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Niteo's Environmental Health and Safety Department (1-844-696-4836).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient

	Page: 25
SAFETY DATA SHEET	Revision Date: 07/31/2016
	Print Date: 4/3/2017
	SDS Number: R0253095
Pyroil™ NON-CHLORINATED BRAKE PARTS CLEANER PY400354	Version: 1.2

LCxx : Lethal Concentration, for xx percent of test population
 LDxx : Lethal Dose, for xx percent of test population.
 ICxx : Inhibitory Concentration for xx of a substance
 Ecxx : Effective Concentration of xx
 N.O.S.: Not Otherwise Specified
 OECD : Organization for Economic Co-operation and Development
 OEL : Occupational Exposure Limit
 P-Statement : Precautionary Statement
 PBT : Persistent , Bioaccumulative and Toxic
 PPE : Personal Protective Equipment
 STEL : Short-term exposure limit
 STOT : Specific Target Organ Toxicity
 TLV : Threshold Limit Value
 TWA : Time-weighted average
 vPvB : Very Persistent and Very Bioaccumulative
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
 DOT : Department of Transportation
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
 HMIRC : Hazardous Materials Information Review Commission
 HMIS : Hazardous Materials Identification System
 NFPA : National Fire Protection Association
 NIOSH : National Institute for Occupational Safety and Health
 OSHA : Occupational Safety and Health Administration
 PMRA : Health Canada Pest Management Regulatory Agency
 RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System